COBBLESTONE





LIVE LIFE IN COLOR!

paving stones & retaining walls

paver-shield™

FEATURES

- Octagonal shape with small square
 Flat surface
- Chamfered edges





SPECIFICATIONS

	width	length	thickness	s.f./per pc.	s.f./pallet	pcs./pallet	lbs./pallet	
A	6-1/4"	8-7/8"	2-3/8"	3.6	111	400	3,108	
В	4-3/8"	8-7/8"	2-3/8"	4.5	111	500	3,108	
	Note for Cobblestone Edger. To convert linear feet to square feet, divide linear feet by 3.25							

Cobblestone 8cm available as special order.

INSTALLATION GUIDELINES: SAND

After excavation, compact the subgrade and install a woven separation fabric. Spread and compact a base of clean, graded, dense aggregate (road base). Typical compacted base thickness is 4-6" for pedestrian applications. Pavers are set on a loosely screeded 1" bed of graded, clean concrete sand. Maintain a joint size of 1/16" – 3/16". When pavers are set, compact paving stones into sand with mechanical plate vibrator. Joint sand may be spread over paving stones during compaction. Installed pavers should be set 1/8" to 1/4" above final elevations to compensate for any potential settlement. Spread clean dry sand over surface and broom sweep to fill joints.



charcoal



fire island blend



red




granite city blend



autumn blend*

Edgers available in Charcoal, Granite City, Red and Fire Island

CROSS-SECTION OF TYPICAL INSTALLATION





Nicolock's Paver-Shield™

· Ultra-dense surface with more color and more protection. Nicolock has color from top to bottom throughout the paver ensuring a lifetime of beauty. Iron oxide pigments are guaranteed not to fade!

NOTE: All measurements are nominal. Variance in square footage or linear footage coverage can be up to 5% depending on joint width. The possible occurrence of efflorescence does not affect the structural integrity of the product. Efflorescence is a normal occurrence in concrete products and will dissipate with normal weathering. The use of concrete as a base or setting bed may increase the possibility of efflorescence.

CAUTION: Always use a plate compactor with a pad when installing any textured paving stone.











