
COUNTRY 6X6 AND 6X9



LIVE LIFE IN COLOR!

paving stones & retaining walls

paver-shield™

COUNTRY 6X6 AND 6X9

FEATURES

Slightly dimpled surface • Textured edges




SPECIFICATIONS							
	width	length	thickness	s.f./per pc.	s.f./pallet	pcs./pallet	lbs./pallet
A	6"	6"	2-3/8"	4	120	480	3,360
В	6"	9"	2-3/8"	2.7	113	300	3,164

INSTALLATION GUIDELINES: SAND

After excavation, compact the subgrade and install a woven separation fabric. Spread and compact a base of clean, graded, dense aggregate (road base). Typical compacted base thickness is 4-6" for pedestrian applications. Pavers are set on a loosely screeded 1" bed of graded, clean concrete sand. Maintain a joint size of 1/16" – 3/16". When pavers are set, compact paving stones into sand with mechanical plate vibrator. Joint sand may be spread over paving stones during compaction. Installed pavers should be set 1/8" to 1/4" above final elevations to compensate for any potential settlement. Spread clean dry sand over surface and broom sweep to fill joints.

CROSS-SECTION OF TYPICAL INSTALLATION



NOTE: All measurements are nominal. Variance in square footage or linear footage coverage can be up to 5% depending on joint width. The possible occurrence of efflorescence does not affect the structural integrity of the product. Efflorescence is a normal occurrence in concrete products and will dissipate with normal weathering. The use of concrete as a base or setting bed may increase the possibility of efflorescence.

CAUTION: Always use a plate compactor with a pad when installing any textured paving stone.



adobe blend antiqued



charcoal antiqued**



golden brown blend antiqued



granite city blend antiqued



terra cotta blend antiqued



autumn blend antiqued*



bayberry blend antiqued*



















📻 in 🏙 🧚 😰 🗑 | nicolock.com

