

# THE MONTAUK



THE MONTAUK: Oyster Blend  
Walkway: Alpine Ridge in Pennsylvania Blue (Random Pattern)

LIVE LIFE IN COLOR!




# THE MONTAUK



## FEATURES

- Multi-size irregular shapes • Textured surface
- Textured edges • No spacer lugs • Sizes not sold separately



## COLOR SELECTION



charcoal



granite city blend



oyster blend\*

\* denotes premium color

\*\* denotes deluxe color


## SPECIFICATIONS

	width	length	thickness	s.f./per pc.	s.f./pallet	pcs./pallet	lbs./pallet
<b>A</b>	2-3/4"	3-1/4"	2-3/8"		65	116	2,592
<b>B</b>	2-3/4"	4"	2-3/8"			120	
<b>C</b>	3"	4"	2-3/8"			126	
<b>D</b>	3-5/8"	4"	2-3/8"			99	
<b>E</b>	4"	4"	2-3/8"			126	

## INSTALLATION GUIDELINES: SAND

After excavation, compact the subgrade and install a woven separation fabric. Spread and compact a base of clean, graded, dense aggregate (road base). Typical compacted base thickness is 4-6" for pedestrian applications. Pavers are set on a loosely screeded 1" bed of graded, clean concrete sand. Maintain a joint size of 1/16" - 3/16". When pavers are set, compact paving stones into sand with mechanical plate vibrator. Joint sand may be spread over paving stones during compaction. Installed pavers should be set 1/8" to 1/4" above final elevations to compensate for any potential settlement. Spread clean dry sand over surface and broom sweep to fill joints.

## CROSS-SECTION OF TYPICAL INSTALLATION



### Nicolock's Paver-Shield™

- Ultra-dense surface with more color and more protection. Nicolock has color from top to bottom throughout the paver ensuring a lifetime of beauty. Iron oxide pigments are guaranteed not to fade!

**NOTE:** All measurements are nominal. Variance in square footage or linear footage coverage can be up to 5% depending on joint width. The possible occurrence of efflorescence does not affect the structural integrity of the product. Efflorescence is a normal occurrence in concrete products and will dissipate with normal weathering. The use of concrete as a base or setting bed may increase the possibility of efflorescence.

**CAUTION:** Always use a plate compactor with a pad when installing any textured paving stone.